

GENERATING **PRIME** SET

DIESEL GENSET 250kVA (Prime Power)

PRD250D
250kVA

50Hz



Specification, picture, dimension may change without notice due to product improvement.

Engine Specs

Type	: DEUTZ TCD 2013 L06 4V
Power Output Gens. [kW]	: 200
Electrical Output Gens. [kVA]	: 250
Speed [Rpm] / Frequency [Hz]	: 1500 / 50
No of cylinders	: 6
Displacement [l]	: 7.15
Bore/Stroke [mm]	: 108 / 130
Injection System	: Common Rail
Compression Ratio	: 17
Mean Effective pressure [bar]	: 28
Cooling System	: Water cooling with Radiator
Fuel Consumption [l/h]	: 47.4 (100% Load)
Oil Capacity [l]	: 20

Alternator Specs


Type [3 Phases, Single Bearing]	: LEROY SOMER : STAMFORD UCDI.274 K or : MECC ALTE (or equivalent)
Rated Output [kVA]	: 250
Speed [Rpm] / Frequency [Hz]	: 1500 / 50
Voltage [V]	: 400
Insulation	: Class H
Protection	: IP 23 (other protection on request)

Accessories

Radiator Cooling	: as DEUTZ standard
Radiator & Engine Capacity	: 98 L
Digital Control Panel, consist of	: DEEP SEA ELECTRONICS (DSE 4520) Module, parameter : •Volt meter, •Auto Start Control (AMF), •Hour meter, •Speed Control, •Engine lube oil pressure gauge, •Engine coolant Temperature gauge) ,
Batteries	: Start key switch : Charging control lamp : Control fuse : Emergency Stop Button : 24Volts, 2 x 120Ah (minimum capacity) : Set of Connection cables and Cable terminals
Exhaust System	: Industrial exhaust silencer
Air Filter	: Dry Type
Baseframe	: Steel Channel construction (include daily tank for 8hrs operation)
Engine and Alternator Mounting	: Rubber metal elements
Set of Operation books	: User's Manual

Genset Dimension and Weight

Dimension Approx. [LxWxH]	: 2400mm x 1000mm x 1700mm
Dry Weight Approx.	: 1900kg



TRIANA BINTANG Pts, Ltd.
DEUTZ AG Authorized distributor.

Telp : 62-24-658-1760 Fax : 62-24-658-1759
Wisma Energie
Jl.Raya kaligawe Km.7 no 311
Semarang – Central Java
Indonesia

GENERATING
PRIME SET