

GENERATING **PRIME** SET

DIESEL GENSET 200kVA (Prime Power)



Specification, picture, dimension may change without notice due to product improvement.

Engine Specs

Type	: DEUTZ BF6M1013FC
Power Output Gens. [kW]	: 160
Electrical Output Gens. [kVA]	: 200
Speed [Rpm]	: 1500
Frequency [Hz]	: 50
No of cylinders	: 6 (in-line)
Displacement [l]	: 7.15
Bore/Stroke [mm]	: 108 / 130
Governor	: Electronic
Compression Ratio	: 18.1 : 1
Cooling System	: Water cooling with Radiator
Fuel Consumption [l/h]	: 45.9 (100% Load)
Oil Capacity [l]	: 20

Alternator Specs

Type [3 Phases, Single Bearing]	: STAMFORD UCI274H
	: LSA 46.3 S3 (or equivalent)
Rated Output [kVA]	: 200
Speed [Rpm]	: 1500
Frequency [Hz]	: 50
Insulation	: Class H
Protection	: IP 23

Accessories

Radiator Cooling	: as DEUTZ standard
Coolant Capacity (incl. radiator)	: 23.1 L
Digital Control Panel Feature	: DEEP SEA ELECTRONICS (DSE 4520) : •Large back-lit icon LCD display•Heated display option•3-phase generator sensing•600V ph-ph nominal system compatibility•Generator & load power monitoring (kW, kV A, kV Ar, pf) •Generator overload protection•Configurable inputs & outputs•Fuel and start outputs (configurable on CAN) •Configurable DC, volt-free and staged loading outputs•CAN & alternator speed sensing•Configurable event log (50) •DSE configuration suite PC software
System Volt	: 12Volts
Exhaust System	: Set of Connection cables and Cable terminals
Air Filter	: Industrial exhaust silencer
Baseframe	: Dry Type
Engine and Alternator Mounting	: Steel Channel construction (include daily tank for 8hrs operation)
Set of Operation books, consist of	: Rubber metal elements : Engine operating instruction : Certificate of Origin : Alternator operating instruction : Genset Test Report

Genset Dimension and Weight

Open Type

Dimension Approx. [LxWxH] : **2400mm x 1000mm x 1700mm**

Operating Weight Approx. : **1792kg**

Silent Type

Dimension Approx. [LxWxH] : **3500mm x 1300mm x 1800mm (without muffler)**

Dry Weight Approx. : **2450kg**

TRIANA BINTANG Pts, Ltd.
DEUTZ AG Authorized distributor.

Head Office :

Mlaten Trenggulun 82-84
Telp : 62-24-3541080/3519324
Fax : 62-24-3541085
Semarang – Central Java
Indonesia

Workshop :

Wisma Energie, Jl.Raya kaligawe Km.7 no 311
Telp : 62-24-658-1760
Fax : 62-24-658-1759
Semarang – Central Java
Indonesia

GENERATING
PRIME SET