# GENERATING PRIME SET

# **DIESEL GENSET 30kVA (Prime Power)**



**Engine Specs** 

Type : **DEUTZ F4M2011** 

Power Output Gens. [kW] : 24 Electrical Output Gens. [kVA] : 30

Speed [Rpm] / Frequency [Hz] : 1500 / 50

No of cylinders : 4 (in-line)
Displacement [I] : 3.11

Bore/Stroke [mm] : 3.11

Governor : Mechanical Compression Ratio : 19:1

Cooling System : Oil cooled

Fuel Consumption [I/h] : 8.9 (100% Load)

Oil Capacity [I] : 9

**Alternator Specs** 

Type [3 Phases, Single Bearing] : **STAMFORD PI 144 G** /

: Leroy Somer LSA42.3VS3

Rated Output [kVA] : 30

Speed [Rpm] / Frequency [Hz] : 1500 / 50

Voltage [V] : 400 Insulation : Class H Protection : IP 23

### **Accessories**

Oil Cooled : as DEUTZ standard

Genset Control Panel, consist of : Engine running hour meter

: Tachometer : Ampere meter : Volt meter

: Engine lube oil pressure gauge

: Start key switch

: Charging control lamp

: Control fuse

: Emergency Stop Button

Batteries : 12Volts,

: Set of Connection cables and Cable terminals

Exhaust System : Industrial exhaust silencer

Baseframe : Steel Channel construction (include daily tank

for 8hrs operation)

Engine and Alternator Mounting : Rubber metal elements
Set of Operation books, consist of : Engine operating instruction

: Certificate of Origin

: Alternator operating instruction

: Genset Test Report

## **Genset Dimension and Weight**

**Open Type** 

Dimension Approx. [LxWxH] : 1550mm x 755mm x 1200mm

Dry Weight Approx. : 716kg

Silent Type

Dimension Approx. [LxWxH] : 2000mm x 1000mm x 1200mm

Dry Weight Approx. : 894kg

# TRIANA BINTANG Pts, Ltd. DEUTZ AG Authorized distributor.

Head Office : Workshop :

Mlaten Trenggulun 82-84 Telp: 62-24-3541080/3519324

Fax: 62-24-3541085 Semarang – Central Java

Indonesia

Wisma Energie, Jl.Raya kaligawe Km.7 no 311

Telp: 62-24-658-1760 Fax: 62-24-658-1759 Semarang – Central Java

Indonesia

